

Model No. LD780B60C18
780nm 60mW 80°C Laser Diode in TO-18 Ø5.6mm Package

FEATURES

- 780nm 60mW CW AlGaAs Laser Diode
- Package: TO-18 (dia. 5.6mm)
- Built-in photodiode for monitoring laser diode

APPLICATIONS

- Industrial optical module
- Sensor

ABSOLUTE MAXIMUM RATINGS

PARAMETER	SYMBOL	CONDITION	RATING	UNIT
OPTICAL OUTPUT POWER	P_O	CW	80	mW
REVERSE VOLTAGE (LD)	V_{RL}	-	2	V
REVERSE VOLTAGE (PD)	V_{RD}	-	30	V
OPERATING TEMPERATURE	T_{opr}	-	-10 to +80	°C
STORAGE TEMPERATURE	T_{stg}	-	-40 to +85	°C

ELECTRICAL AND OPTICAL CHARACTERISTICS ($T_c = 25^\circ\text{C}$)

PARAMETER	SYMBOL	MIN.	TYP.	MAX.	UNIT	CONDITIONS
LASING WAVELENGTH	λ_p	770	780	790	nm	$P_O = 60\text{mW}$
THRESHOLD CURRENT	I_{th}	-	30	50	mA	-
OPERATING CURRENT	I_{op}	-	90	120	mA	$P_O = 60\text{mW}$
DIFFERENTIAL EFFICIENCY	η	0.7	1.0	1.3	mW/mA	$P_O = 30\text{--}60\text{mW}$
OPERATING VOLTAGE	V_{op}	-	2.2	2.5	V	$P_O = 60\text{mW}$
MONITOR CURRENT	I_m	0.1	0.3	0.8	mA	$P_O = 60\text{mW}$
PARALLEL DIVERGENCE ANGLE	$\Theta_{//}$	8	10	12	deg	$P_O = 60\text{mW}$
PERPENDICULAR DIVERGENCE ANGLE	$\Theta_{\perp}$	16	18	20	deg	$P_O = 60\text{mW}$
PARALLEL FFP DEVIATION ANGLE	$\Delta \Theta_{//}$	-2	0	+2	deg	
PERPENDICULAR FFP DEVIATION ANGLE	$\Delta \Theta_{\perp}$	-3	0	+3	deg	
EMISSION POINT ACCURACY	$\Delta x \Delta y \Delta z$	-60	0	+60	um	

Note: The above specifications are subject to change without notice.



19608 Camino De Rosa, Walnut, CA 91789, USA | Tel: (909)718-0999 | Fax: (909)718-0998 |
E-mail: info@lasermate.com | URL: <http://www.lasermate.com>