

**Model No. LD830C200C16**  
**830nm 200mW 60°C Laser Diode in TO-18 Ø5.6mm Package**

**FEATURES**

- 830nm 200mW CW AlGaAs Laser Diode
- Package: TO-18 (dia. 5.6mm)
- Built-in photodiode for monitoring laser diode

**APPLICATIONS**

- Motion recognition sensor
- Industrial optical module

**ABSOLUTE MAXIMUM RATINGS**

| PARAMETER             | SYMBOL    | CONDITION | RATING     | UNIT |
|-----------------------|-----------|-----------|------------|------|
| OPTICAL OUTPUT POWER  | $P_O$     | CW        | 210        | mW   |
| REVERSE VOLTAGE (LD)  | $V_{RL}$  | -         | 2          | V    |
| REVERSE VOLTAGE (PD)  | $V_{RD}$  | -         | 30         | V    |
| OPERATING TEMPERATURE | $T_{opr}$ | -         | -10 to +60 | °C   |
| STORAGE TEMPERATURE   | $T_{stg}$ | -         | -40 to +85 | °C   |

**ELECTRICAL AND OPTICAL CHARACTERISTICS ( $T_c = 25^\circ\text{C}$ )**

| PARAMETER                         | SYMBOL                       | MIN. | TYP. | MAX. | UNIT  | CONDITIONS           |
|-----------------------------------|------------------------------|------|------|------|-------|----------------------|
| LASING WAVELENGTH                 | $\lambda_p$                  | 815  | 825  | 840  | nm    | $P_O = 200\text{mW}$ |
| THRESHOLD CURRENT                 | $I_{th}$                     | 30   | 50   | 85   | mA    | -                    |
| OPERATING CURRENT                 | $I_{op}$                     | 180  | 220  | 240  | mA    | $P_O = 200\text{mW}$ |
| DIFFERENTIAL EFFICIENCY           | $\eta$                       | 0.8  | 1.0  | 1.4  | mW/mA | $P_O = 200\text{mW}$ |
| OPERATING VOLTAGE                 | $V_{op}$                     | 1.8  | 2.1  | 2.5  | V     | $P_O = 200\text{mW}$ |
| MONITOR CURRENT                   | $I_m$                        | 0.01 | 0.3  | 1.0  | mA    | $P_O = 200\text{mW}$ |
| PARALLEL DIVERGENCE ANGLE         | $\Theta_{//}$                | 5    | 9    | 13   | deg   | $P_O = 200\text{mW}$ |
| PERPENDICULAR DIVERGENCE ANGLE    | $\Theta_{\perp}$             | 12   | 18   | 24   | deg   | $P_O = 200\text{mW}$ |
| PARALLEL FFP DEVIATION ANGLE      | $\Delta \Theta_{//}$         | -2   | 0    | +2   | deg   | $P_O = 200\text{mW}$ |
| PERPENDICULAR FFP DEVIATION ANGLE | $\Delta \Theta_{\perp}$      | -3   | 0    | +3   | deg   | $P_O = 200\text{mW}$ |
| EMISSION POINT ACCURACY           | $\Delta x \Delta y \Delta z$ | -60  | 0    | +60  | um    |                      |


**Note: The above specifications are subject to change without notice.**




**LASERMATE GROUP, INC.**

**The Friend of Lasers**

## MECHANICAL OUTLINE (unit: mm)



## Pin Configuration



## PRECAUTIONS

- Do not operate the device above maximum ratings. Doing so may cause unexpected and permanent damage to the device.
- Take precautions to avoid electrostatic discharge and/or momentary power spikes. A change in the characteristics of the laser or premature failure may result.
- Proper heat sinking of the device assures stability and lifetime. Always ensure that maximum operating temperatures are not exceeded.
- Observing visible or invisible laser beams with human eye directly, or indirectly, can cause permanent damage. Use a camera to observe the laser.
- No laser device should be used in any application or situation where life or property is at risk in the event of device failure.
- Specifications are subject to change without notice. Ensure that you have the latest specification by contacting us prior to purchase or use of the product.

**Note: The above specifications are subject to change without notice.**



19608 Camino De Rosa, Walnut, CA 91789, USA | Tel: (909)718-0999 | Fax: (909)718-0998 |

E-mail: [info@lasermate.com](mailto:info@lasermate.com) | URL: <http://www.lasermate.com>