

Model No. LD980E3WG13 | LD980E3WK13
980nm 3W High Power FP Diode Laser in C-Mount/CoS Package

FEATURES

- 980nm 3W Fabry-Perot cavity semiconductor laser
- Provides beam shaping services, such as fast-axis compression according to customer demands
- Package: C-Mount, CoS



MODEL NUMBER	LD980E3WG13	LD980E3WK13
PACKAGE	C-Mount	CoS

SPECIFICATIONS (T_c = 20°C)

ITEM	PARAMETER	TYP.	UNIT
OPTICAL PARAMETER	Lasing wavelength	980±10	nm
	Output power	3	W
	Spectral width	≤3	nm
	Emitting area width	150	um
	Temperature coefficient	0.30	nm/°C
	Fast axis divergence	<40	deg
	Slow axis divergence	<10	deg
ELECTRICAL PARAMETER	Slope efficiency	≥1.0	W/A
	Threshold current	≤0.75	A
	Operating current	≤3.6	A
	Operating voltage	≤2.0	V
OTHERS	Package	C-Mount / CoS	-
	Operating temperature	15 to 30	°C
	Storage temperature	-40 to +60	°C
	Welding temperature	≤260	°C

Notes:

1. The above specifications are subject to change without notice.
2. Data in the sheet are based on C-mount package heat sink testing.




LASERMATE GROUP, INC.


The Friend of Lasers

MECHANICAL OUTLINE (unit: mm)

LD980E3WG13 (C-Mount Package)



LD980E3WK13 (CoS Package)



PRECAUTIONS

- Do not operate the device above maximum ratings. Doing so may cause unexpected and permanent damage to the device.
- Take precautions to avoid electrostatic discharge and/or momentary power spikes. A change in the characteristics of the laser or premature failure may result.
- Proper heat sinking of the device assures stability and lifetime. Always ensure that maximum operating temperatures are not exceeded.
- Observing visible or invisible laser beams with human eye directly, or indirectly, can cause permanent damage. Use a camera to observe the laser.
- No laser device should be used in any application or situation where life or property is at risk in the event of device failure.
- Specifications are subject to change without notice. Ensure that you have the latest specification by contacting us prior to purchase or use of the product.



19608 Camino De Rosa, Walnut, CA 91789, USA | Tel: (909)718-0999 | Fax: (909)718-0998 |

E-mail: info@lasermate.com | URL: <http://www.lasermate.com>




LASERMATE GROUP, INC.


The Friend of Lasers

TYPICAL CHARACTERISTICS

P-I-V Curve



Spectral Curve



Notes:

1. The above specifications are subject to change without notice.
2. Data in the sheet are based on C-mount package heat sink testing.



19608 Camino De Rosa, Walnut, CA 91789, USA | Tel: (909)718-0999 | Fax: (909)718-0998 |

E-mail: info@lasermate.com | URL: <http://www.lasermate.com>